

X-lite Configuration Guides

Version 1.0

Yeastar Information Technology Co. Ltd.

Ensure that you have created the extension that you wish to use with the phone in MyPBX first. Take note of the Extension field and the password that you have entered for the extension.

 100 100 E 150 (d-f-d)			
192.168.5.150 (default)	500	500	
			<u>R</u> emove
			Properties
			Make <u>D</u> efault

Figure 1-1

Configuring a SIP account in X-Lite

1. Now start up X-Lite. The first time you start it up, it will bring up the 'Sip Accounts' dialog. Click 'Add' to create a new account.

Properties of Account 1					
Account Voicemail Topology Presence Advanced					
CUser Details	· · · ·				
Display Name	500				
User name	500				
Password	********				
Authorization user name	500				
Domain	192.168.5.150				
Domain Proxy					
Register with domain and receive incoming calls					
Send outbound via:					
domain Oroxy Address					
O proxy Address					
Dialing plan	#1\a\a.T;match=1;prestrip=2;				
	确定 取消 应用 (<u>a</u>)				



Figure 1-2

SIP account properties

- 1) Now enter a Display name.
- 2) In the User name field, enter the extension number.
- 3) In the Password field enter the SIP password.
- 4) In the Authorized User name field, enter the extension number again.
- 5) In the 'Domain' field enter the Network address IP of MyPBX server.
- 6) In the Domain proxy section, ensure that you have selected 'Register with domain and receive inbound calls'. Select Target 'Domain'.
- 7) Click OK to save the account.

X-Lite showing successful registration with the phone system



Figure 1-3

8) X-Lite now tries to register with MyPBX. If successful, you will see a screen similar to the one in the screenshot.

<Finish>

